



Technical specifications

meets the requirements of EN ISO 10582

	Total thickness	EN 428	2.0 mm
	Wear layer thickness	EN 429	0.5 mm
	Commercial use	EN ISO 10874	Class 34
	Industrial use	EN ISO 10874	Class 43
	Roll width	EN 426	2.0 m
	Roll length	EN 426	≤ 25 m
	Total weight		350 g/m ²
	Dimensional stability	EN 434	≤ 8%
	Residual indentation	EN 434	≤ 0.10 mm
	Castor chair continuous use	ISO 4918 / EN 425	pass
	Light fastness	ISO 105-B02	≥ 6
	Flexibility	EN ISO 24344	ø 10 mm
	Resistance to chemicals	EN 423	very good
	Slip resistance	DIN 51130	R9
	Suitable for floor heating		Yes*
	Indoor Air Emissions: TVOC after 28 days	ISO 16516	≤ 0.02 mg/m ³
	Life Cycle Assessment		LCA is the foundation for securing the lowest environmental impact
	Creating better environments		
	Recycled content		contains up to 60% recycled content in the backing
	meets the requirements of EN 14041		EN 14041 CE 0200105-DoP-306
	Reaction to fire	GB8624-2012	B _s +1, L, NCS
	Slip resistance	DIN 51130	μ ≥ 0.30

SGS



CERTIFIED BY
SCS Global Services



#0821
ISO/IEC 17065
Product Certification Body