

# SR Classic / Classic SD

## Multipurpose R10 Safety Flooring




















### Description

High Specification R10 Safety Flooring  
 Suitable for use in all Dry and Wet areas where there is a requirement for wear and slip resistance  
 Available in 2 and 2.5mm thickness and Classic SD version for greater Static Performance (where required)

### Warranty

The flooring has a minimum Warranty period of 10 years (extended warranties available against specific use details)  
 The above Warranty is subject to the products being specified, installed and maintained in accordance with our recommendations (copies available on request)

### Technical

Flooring Type		EN 13845	Safety Flooring
Roll Dimensions		EN ISO 24341	2.0m x 20m = 40m <sup>2</sup>
Overall Thickness		EN ISO 24346	1.8mm 2.0mm 2.5mm
Weight		EN ISO 23997	2.25kgs 2.45kgs 3.10kgs
Classification		EN 13845 EN 685	34 & 43
Indentation		EN ISO 24343-1	≥0.10mm
Wear Resistance		EN 13845 Annex D	≤10%particles lost over 50,000 cycles
SLIP RESISTANCE		EN 13845 Annex C CEN/TS 16165:2016 (96 & 57) EN 13893 DIN 55130	ESf & ESb ≥36 DS R10
Flexibility		ISO 24344 Method A	PASS 20mm Mandrel
Dimensional Stability		EN ISO 23999	<0.4%
Chemical Resistance		EN ISO 26987	Good
Colour Fastness		EN ISO 105-B02 Method 3	≥6
FIRE Performance		EN 13501-1 ISO 9239-1 ISO 11925-2	Class Bfl-s1 Critical Radiant Flux≥8kW/m <sup>2</sup> PASS
Electrical Behaviour		EN 1815 EN 1081	< 2kV PASS ≤ 107Ω (SR Classic SD)
Castor chair test		EN 425	PASS
Seam Strength		EN 684	PASS
Thermal Conductivity (Underfloor Heating)		EN ISO 12667	Suitable
TVOC Emissions after 28 Days		EN ISO 16000-9	> 40 μ/m <sup>3</sup>
CE Marking		EN 14041	CE Marking